

BASKET FILTER HOUSING CUSTOM MADE

GV basket filters are sized and made according to customer specifications. Many materials can be used for their realization such as: Stainless Steel, Carbon Steel and Special Steel (Monel, Duplex, Super Duplex, etc.). We design the most common international standards for design: ASME Sec. VIII, EN13445-3, PED94 / 9. On each filter, various surface treatments can be carried out, such as internal and external painting cycles, passivation and pickling..



Applications

Oil & Gas

• Refinery Process Fluids

Chemical & Petrolchemical

Process Fluids

Water Treatment

Industrial Process Water Filtration

Power Generation

• Process Fluids • Gas Separetion & Treatment • Water Treatment

Industrial

· Paints Water Inks Production



Characteristics:

- Construction materials:

Carbon steel

Stainless steel

(other materials available as option)

- Design according to: ASME Sect. VIII Div. 1

EN 13445

VSR

(other calculation code available as option)

- Suitable for filtration of both liquids and gas Gr. 1 and 2
- Conform to 97/23/CE PED Directive
- Conform to 94/9/CE ATEX Directive
- Available with U-Stamp certification

- Top cover closure:

ANSI or EN flanges

Swing bolts - eye bolts type

Swing bolts - Rathmann type


Quick opening closure

- Side by side in/out


(other nozzles arrangement available as option)

- In/out connections up to 24" (DN 600)
- Perforated plate with wire mesh or wedge-wire basket
- -Pleated or smooth basket type option available

Туре	Connections	Indicative dimensions (mm)			
	DN Standard	Α	В	С	D
ВС	25	200	380	500	450
	40	200	380	500	450
	50	200	400	550	450
	65	200	400	550	450
	80	200	450	650	550
	100	250	600	800	550
	150	250	700	950	600
	200	300	750	1000	750
	250	350	800	1100	800
	300	460	950	1300	850
	350	500	1000	1400	950
	400	500	1000	1450	1050
	450	500	1050	1500	1150
	500	500	1100	1550	1200



Ordering Info



^{*} Contact GV Filtri for more information about Materials and Dimensions avaibility